


GT 3 Installation Hub – Models 10-7014, 20-7014

Parts List

- Hub Assy (1)
- Mounting screws (3)
- Ground wire (1)
- Sleeve (1)
- Washer (1)



FITMENT:

Autos

Dodge	1970-87	All Models w / standard column
Chrysler		(except Omni, Horizon, Rampage, Daytona,
Plymouth		Shelby, Charger, Shadow, Sundance)

Trucks

Dodge	1970-87	Dodge Plymouth 2wd standard column
Chrysler		Fullsize pick-ups, Dakota
Plymouth	1978-87	Vans with standard column including Caravan and Voyager

Notice

Airbag equipped vehicles: GT Performance Products steering wheels and hubs are **not** designed for use on Airbag equipped vehicles. **Due to Safety and Legal reasons**, we do not recommend changing, altering or removing the airbag from any vehicle.


PRE-INSTALLATION INSTRUCTIONS

- A) Read all instructions completely prior to installation process!
- B) Align wheels on vehicle straight ahead and disconnect battery.
- C) Removal of Original or Custom Steering Wheel: Refer to shop manual for your vehicle or manufacturer of custom steering wheel.
NOTE: A steering wheel or gear puller may be required.

INSTALLATION

- 1) Position shaft sleeve onto shaft before installing hub.
- 2) Note "top" marking on hub (2 vertical dimples which indicate top), and position hub onto shaft.
- 3) Position steering wheel onto hub, carefully routing wire thru hole on right side of wheel, and install shaft nut loosely to hold assembly in position.
- 4) Place horn button base w/ O-ring onto wheel and install using the (3) three mounting screws, placing the ground wire under one of the screws. (Photo C)

Photo C



TORQUE REQUIREMENTS
 Shaft nut: 25 / 30 ft. lbs.
 Mounting screws: 10 / 12 ft. lbs.

- 5) Tighten shaft nut and mounting screws. **CAUTION: Do not over tighten mounting screws; this will cause damage to the hub.**
- 6) Connect wires to bottom of horn button and carefully push horn button onto base over O-ring until the horn button is flush with surface of wheel. (Photo D) Note: If necessary, slightly wet the O-ring to ease installation.

CAUTION: Be careful not to pinch wires when installing horn button onto base.

Photo D



- 7) Reconnect battery and test operation of horn and turn signal canceling.

NOTE: TO REMOVE HORN BUTTON: Insert small, non-marring plastic blade, or screw driver between notch on bottom of horn button and wheel surface and carefully pry to release.

**GT Performance Products LLC
 Limited Warranty Policy**

We warrant our products ninety (90) days from the date of original purchase to be free from defects in material and workmanship. If, during this period, the product fails under normal usage because of a manufacturing defect, then we will replace or repair the item. To obtain repair or replacement under the terms of this warranty, notify us at, GT Performance Products, 2070 Floyd Street, Burbank, CA 91504. Proof of purchase and date of purchase are required to validate warranty.

All implied warranties, including the warranty of merchantability, are limited to the same ninety-day period from date of purchase. We are not liable for any consequential loss or property damage arising from any use of this product. This warranty gives you specific legal rights, and you may also have other rights which vary from state to state. Offer good in U.S.A. and Canada only.

NOTICE:

For your own safety, do **not** use this product for any competitive or racing purposes; Racing does not constitute intended usage and therefore makes this warranty void.